



CSF506

Ceiling speaker with fire dome 100V

Highlights:

- Multi-tapping 100V line transformer
- 5" full range driver
- Steel front grill with flame retardant materials
- Steel fire protection dome


The CSF506MK2 is a fire-protected ceiling speaker with a 5" cone, capable of producing a power of 6 Watt. It ensures a good reproduction of speech and background music. It is fitted with a 100V line transformer with power taps for 6 Watt and 3 Watt to be used in large 100V PA systems. The speaker is equipped with a special steel fire protection dome fitted around the speaker and a steel front grill with flame retardant materials. This provides the fire protection according to the EN60849 standard.

Applications:

- Bars, restaurants
- Retail
- Hotels
- Public facilities
- Corporate spaces



Voltage:



System specifications:

| | | |
|----------------------------|------------------------|---------------------|
| Speaker type | | Broadband |
| Max. Power | | 10 W |
| RMS Power | | 6 W |
| Line Transformer Tappings | 1 | 6 W / 1666 Ω |
| | 2 | 3 W / 3333 Ω |
| Impedance | | 8 Ω |
| Frequency | Response (\pm 3 dB) | 90 Hz - 18 kHz |
| Sound Pressure (Max. W/1m) | | 90 dB |
| Drivers | | 5" |

Product Features:

| | |
|---------------------|--------------------------------------|
| Dimensions | 180 x 127 mm (Ø x D) |
| Cut-out measurement | 160 mm (Ø) |
| Weight | 1.300 kg |
| Construction | Steel fire protection dome |
| Front finish | Steel with flame retardant materials |

Shipping & Ordering:

Packaging Cardboard box

