



EDL-82HQ

Order No.: 0163440

PRODUCTINFOS

PA hi-fi wall and ceiling speaker, 30 W

- 100 V line technique or 8 Ω operation
- 2-way version with coaxial dome tweeter
- 20 cm (8") bass speaker with waveguide and 25 mm (1") silk dome
- Pivoting tweeter via ball joint
- Excellent sound characteristics
- Stylish flush fit protective metal grille with slim plastic frame
- Protective grille magnetically attached to speaker front
- For a wall thickness/ceiling thickness from 6 to 35 mm

TECHNICAL SPECIFICATIONS

EDL-82HQ

Impedance (Z)	8 Ω
Transmission method	100 V or low-impedance
Frequency range	30-20,000 Hz

EDL-82HQ

Resonant frequency (fs)	40 Hz
Power rating (RMS)	50 W (8 Ω) 30/16/8/4 W (100 V)
Peak music power output (MAX)	100 W
Sensitivity	89 dB/W/m
Mounting cutout	Ø 252 mm
Mounting depth	97 mm
Dimensions	Ø 295 mm x 100 mm
Outside diameter	Ø 295 mm
Width	Ø 295 mm
Depth	100 mm
Colour	white/black
Admiss. ambient temp.	0-40 °C
Weight	2 kg
Packing unit	1
Type of speaker	200
Packing dimensions (W x H x L)	0.315 x 0.135 x 0.315 m
Gross weight	2.47 kg
Net weight	2.07 kg