



EDL-156

Order No.: 0161910

PRODUCTINFOS

Weatherproof PA ceiling speakers,

heat-resistant up to 100 °C. For applications in saunas and swimming pool areas.

- 100 V line technique
- 2-way system with dome tweeter
- Excellent sound
- White plastic housing
- Weatherproof speaker cone
- Tested according to ASTM B117 (400 h salt spray test)
- For a ceiling thickness from 2 to 25 mm

TECHNICAL SPECIFICATIONS

EDL-156

| | |
|---------------------|--------------------|
| Transmission method | 100 V |
| Frequency range | 60-20,000 Hz |
| Power rating (RMS) | 15/10/5/2.5/1.25 W |

EDL-156

| | |
|--------------------------------|------------------------|
| Sensitivity | 88 dB/W/m |
| Mounting cutout | Ø 190 mm |
| Mounting depth | 75 mm |
| Dimensions | Ø 226 mm x 100 mm |
| Outside diameter | Ø 226 mm |
| Width | Ø 226 mm |
| Depth | 100 mm |
| Colour | white |
| Protective class | IP65 |
| Admiss. ambient temp. | -20 °C to +100 °C |
| Weight | 1.1 kg |
| Packing unit | 1 |
| Type of speaker | 180 |
| Packing dimensions (W x H x L) | 0.225 x 0.095 x 0.23 m |
| Gross weight | 1.249 kg |
| Net weight | 1.083 kg |